

We Claim:

1. A method for dispensing a fabric conditioner in a dryer, the dryer having an inner surface, comprising:

a. attaching a plate member to the inner surface of the dryer, said plate member having a front side, a back side, and an attachment member, said back side having an adhesive, said adhesive connecting said back side to the inner surface of the dryer;

b. attaching a product carrier to said front side of said plate member, said product carrier having a mating member, a first side, and a second side, said mating member being configured and arranged to engage said attachment member thereby releasably connecting said plate member and said product carrier, said product carrier carrying the fabric conditioner and being replaceable, wherein a substantial portion of the fabric conditioner extends from said first side of said product carrier away from said plate member and said second side of said product carrier faces said front side of said plate member;

c. allowing the fabric conditioner to become depleted after repeated use in the dryer; and

d. removing said product carrier from said plate member and attaching a second product carrier carrying a second fabric conditioner to said plate member.

2. A method of dispensing a fabric conditioner in a dryer, comprising:

a. casting a fabric conditioner onto a product carrier, said fabric conditioner having rounded edges;

b. attaching a plate member to a fin of a dryer;

c. attaching said product carrier to said plate member;

d. allowing said dryer to run through a dryer cycle; and

e. dispensing a consistent, optimum dose of said fabric conditioner from an initial cycle to a final cycle until said fabric conditioner has become depleted.